



WIRE CHART

P3	P4	P1	P2
PIN 1 GND(接地)	PIN 1	PIN 13~15 YELLOW	PIN 1
PIN 2	PIN 2	PIN 4~6 BLACK	PIN 3
PIN 3	PIN 3	PIN 7~9 RED	PIN 4
PIN 4 GND(接地)	PIN 4	PIN 10~12 BLACK	PIN 2
PIN 5	PIN 5		
PIN 6	PIN 6		
PIN 7 GND(接地)	PIN 7		

TEST REQUEST:
 ■ 1.OPEN SHORT 100%
 ■ 2.CT≤2Ω IS≥5MΩ
 ■ 3.HV:DC 300V TIME: 0.1SEC

BACK VIEW

NO.	DESCRIPTION	MATERIAL	QTY
11	Mark H.S TUBE	White PE Mark H.S TUBE φ6*40 Print:ODD , φ7*40 Print:ODD, φ6*50 Print:ODD SATA_CMS	Each 1
10	H.S TUBE	φ6.0*750mm BLACK	1 pcs
9	PE	LD-PE	5g
8	PVC	45P BLACK PVC	9.5g
7	HSG	5016T PH 4.2mm	1 pcs
6	TERMINAL	5016H-2*2P PH4.2mm	4 pcs
5	COON	SATA 7 PIN 180° (Au Plating+Black PBT+Shell Fragment)	1 pcs
4	COON	SATA(7+15)PIN 180° (Au Plating+Black PBT)	1 pcs
3	CABLE	Serial ATA 7P CABLE UL21149[26#(1/0.40TC)*2C+AL] *2F+4D(1/0.32TC) RED L=830MM	1 pcs
2	CABLE	UL1007 20# POWER CABLE (BLACK) L=830MM	2 pcs
1	CABLE	UL1007 20# POWER CABLE (RED,YELLOW) L=830MM	Each 1
	NO. DESCRIPTION	MATERIAL	QTY



Title		SATA 22P TO SATA 7P+4P HSG			
Tolerances	Drawer	Naomi	Part No:		
	Checked	Summer	WCT-STC-053013		
X ±0.15 .X ±0.05	Approved	Macus	Cus. Part No:		
	Date	2017.06.07	WCT-STC-053013		
Angles	Projection	Version	Size	A4	Units
± 3°		A	Scale	1:1	Sheet 1/1