


SPECIFICATION

1. Contact resistance: $\leq 0.03 \Omega$;
2. Insulation resistance: $\geq 100M \Omega$;
3. Withstand voltage: 500VAC ;
4. Temperature: $-45 \sim +85^{\circ} C$

SCHEMATIC



PIN	$\phi 1.0$	$\phi 1.3$
APPD.	A	B

5	CenterPin	1	BRASS	
4	SPRING	1	Mn-STEEL	
3	TERMINAL	1	COPPER	
2	TERMINAL	1		
1	HOUSING	1	PBT	
NO.	DESCRIPTION	QTY	MATERIAL	PLATING



Title	DC JACK					
Tolerances	<i>Drawer</i>	<i>Naomi</i>	<i>Part No:</i>			
<i>Linear</i>	<i>Checked</i>	<i>Summer</i>	WCT-DCJ-313X			
$X \pm 0.15$	<i>Approved</i>	<i>Macus</i>	<i>Cus. Part No:</i>			
$.X \pm 0.05$	<i>Date</i>	2017.06.02	WCT-DCJ-313X			
Angles	<i>Projection</i>	<i>Version</i>	<i>Size</i>	<i>A4</i>	<i>Units</i>	<i>mm</i>
$\pm 3^{\circ}$		A	<i>Scale</i>	1:1	<i>Sheet</i>	1/1