



P.C.B LAYOUT

SCHMATIC



6	TERMINAL	1	STEEL T=0.3	Ni 1~2um;Sn 1~3um Plating
5	TERMINAL	1	STEEL T=0.3	Ni 1~2um;Sn 1~3um Plating
4	COVER	1	PBT	BLACK
3	HOUSING	1	PBT	BLACK
2	SPRING	1	Mn-STEEL T=0.25	Ni 1~2um;Sn 1~3um Plating
1	CenterPin	1	STEEL	Cu 2~3um;Sn 0.5~1um Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING



SPECIFICATION

- Contact resistance:  $\leq 0.03 \Omega$ ;
- Insulation resistance:  $\geq 100M\Omega$ ;
- Withstand voltage: 500VAC ;
- Temperature:  $-45 \sim +85^\circ \text{C}$

Title		DC 470-2.0			
Tolerances	Drawer	Naomi	Part No:		
	Checked	Summer	WCT-DCJ-470		
X ±0.15 .X ±0.05	Approved	Macus	Cus. Part No:		
	Date	2017.06.01	WCT-DCJ-470		
Angles	Projection	Version	Size	A4	Units
± 3°		A	Scale	1:1	Sheet 1/1