



NOTES:

1. MATERIAL
 - 1.1 HOUSING: LCP UL94V-0
 - 1.2 TERMINAL: C5191R-H, T=0.20MM
 - 1.3 SHELL: STAINLESS STEEL, T=0.30MM
2. PLATING
 - 2.1 TERMINAL: UNDERPLATING 50U"~80U" NI; SELECTIVE AU 1U"
3. CHARACTERISTICS:
 - 3.1 CONTACT RESISTANCE: 100mΩ MAX,
 - 3.2 INSULATION RESISTANCE: 1000MΩ MIN.
 - 3.3 OPERATION LIFE: 5000 CYCLES
4. PACKAGE:
 - 4.1 TAPE REEL PACKAGE
 - 4.2 700PCS/REEL
 - 4.3 4200PCS/CARTON



Title		SIM HINGE TYPE WITH CD TYPE					
<i>Tolerances</i>	<i>Drawer</i>	Naomi	<i>Part No:</i>				
<i>Linear</i>	<i>Checked</i>	Summer	WCT-191S06P2WT-1R1				
X ±0.50	<i>Approved</i>	Macus	<i>Cus. Part No:</i>				
.X ±0.30		<i>Date</i>	2017.06.01				
.XX ±0.25	<i>Angles</i>	<i>Projection</i>	<i>Version</i>	<i>Size</i>	A4	<i>Units</i>	mm
± 3°		A	<i>Scale</i>	1:1	<i>Sheet</i>	1/1	