



主要技术特性要求：

1.使用温度范围：

环境温度：-25 ~ +70℃

相对湿度：95%(40℃)

2.额定负荷：2A 100V AC

3.接触电阻：≤ 30mΩ

4.绝缘电阻：≥ 100MΩ

5.耐 压：500V AC (50Hz) 1min

6.插 拔 力：15 ~ 60N

7.寿 命：≥ 5000次

3	插片	1	黄铜	D.Ni/Sn
2	圆针	1	黄铜Ø1.5	D.Ni/Sn
1	底座	1	PBT	
NO.	DESCRIPTION	QTY	MATERIAL	PLATING



<i>Title</i>	Mini Din Jack					
<i>Tolerances</i>	<i>Drawer</i>	<i>Naomi</i>	<i>Part No:</i>			
<i>Linear</i>	<i>Checked</i>	<i>Summer</i>	WCT-DS-2-02BF			
<i>X ±0.15</i>	<i>Approved</i>	<i>Macus</i>	<i>Cus. Part No:</i>			
<i>.X ±0.05</i>	<i>Date</i>	2017.06.27	WCT-DS-2-02BF			
<i>Angles</i>	<i>Projection</i>	<i>Version</i>	<i>Size</i>	<i>A4</i>	<i>Units</i>	<i>mm</i>
± 3°		A	<i>Scale</i>	1:1	<i>Sheet</i>	1/1