



NOTES:

- 1.Rating:250V AC(rms) 3.0A;
- 2.Contact Resistance:≅30Milliohm,After Test:≅50Milliohm;
- 3.Insulation Resistance:≧5000Megohm(DC500V);
- 4.Withstand Voltage:AC1000V for 1Minute;
- 5.Insertion force:44.5N Max;
- 6.Extraction force:3.34~31.15N;
- 7.Life test:500Cycles.
- 8.Operating Temperature:-55°C~+125°C 85%RH Max;
- 9.Storage Temperature:-55°C~+125°C 85%RH Max.

7	TERMINAL 2	1set	COPPER ALLOY	Gold Flash,Solder Area:Matte Sn 80u"
6	TERMINAL 1	2set	COPPER ALLOY	Gold Flash,Solder Area:Matte Sn 80u"
5	SCREW L4-40#UNC	2	STEEL	Nickel 50u" Min plated
4	SHELL COVER	1	SPCC-SD T=0.4mm	Cu:50u"+Nickel 70u" Min
3	SHELL	1	SPCC-SD T=0.4mm	Cu:50u"+Nickel 70u" Min
2	PLASTIC COVER	1	LCP / PA9T	Black
1	HOUSING	1	LCP / PA9T	Black
NO.	DESCRIPTION	QTY	MATERIAL	TREATMENT



Title	SLIM D-SUB 15P					
Tolerances	Drawer	Naomi	Part No:			
Linear	Checked	Summer	WCT-DSC-SLIM01			
X ±0.15 .X ±0.05	Approved	Macus	Cus. Part No:			
	Date	2017.07.03	WCT-DSC-SLIM01			
Angles	Projection	Version	Size	A4	Units	mm
± 3°		A	Scale	1:1	Sheet	1/1