



- 1.MATERIAL:
 INSULATOR: Hi-TEMPERATURE PLASTIC,UL 94V-0,
 COLOR"BLACK
 TERMINAL: COPPER ALLOY,
 SHELL: STAINLESS STEEL,
- 2.PLATING:
 TERMINAL: GOLD FLASH PLATING ON ALL TERMINAL,
 AND 50u" min NICKEL UNDERPLATED ON ALLOVER,
 SHELL:50u" NICKEL UNDERPLATED ON ALLOVER, GOLD FLASH
 ON SOLDER PAD
- 3.SPECIFICATIONS
 INSULATION RESISTANCE: 1000M min.AT DC 500V DC
 WITHSTANDING VOLTAGE: 250V ACrms FOR 1 MINUTE
 CONTACT RESISTANCE: 100mΩ max. AT 10mA/20mV max
 CURRENT RATING: 0.5A
 VOLTAGE RATING: 5.0 vrms
 OPERATING TEMP.RANGE:-40° C+70° C
 MATING CYCLES: 1500 INSERTIONS
- 4.PACKAGE: TAPE REEL, 1500PCS/REEL



RECOMMENDED PCB LAYOUT
 TOL.:±0.05



SIM CARD PIN ASSIGNMENT

PIN	NAME
C1	VCC
C2	RST
C3	CLK
C4	Reserved
C5	GND
C6	Vpp
C7	I/O
C8	Reserved



Title		nano sim push pull 1.20H type		
Tolerances	Drawer	Naomi	Part No:	
Linear	Checked	Summer	WCT-NANO-SIM-1022	
X ±0.15	Approved	Macus	Cus. Part No:	
.X ±0.05	Date	2017.04.01		
Angles	Projection	Version	Size	A4 Units mm
± 3°		A	Scale	1:1 Sheet 1/1