



NOTES:

- MATERIAL SPECIFICATION:
 - HOUSING MATERIAL: SEE PART NO.
 - SHELL: SEE PART NO.
 - PLATING: SEE PART NO.
 - TERMINAL: COPPER ALLOY T:0.25mm
 - PLATING: SEE PART NO.
 - ELECTRICAL CHARACTERISTIC:
 - VOLTAGE CURRENT RATING: 1.5AMP, 30V DC;
 - INSULATION RESISTANCE: 1000MΩMIN;
 - CONTACT RESISTANCE: 30mΩMAX;
 - WITHSTANDING VOLTAGE: 500V AC;
- Mechanical:
- Mating Force: 3.57 KG MAX
 - Unmating Force: 1.02 KG MIN.

Part No: WCT-USB2-01 C F2 O4 1 L4 P 3 S 3 E
 1 2 3 4 5 6 7 8 9 10 11

- Products Distination: USB2=USB 2.0
- Type Difference: C=Side Entry Type
- Specifications Distination: F2=Female To Board
- Pin: O4=O4Pin
- Housing Material: 1=PBT
- Special Practice: L4=侧插短体有卷边0型脚
- Shell Material: P=SPCC
- Housing Color: 3=Black
- Contact Plating: S=Gold Flash
- Package: 3=Tray
- Environmental: E=RoHS(Bright)



Title		USB 2.0 A Type 4P DIP 90°				
Tolerances	Drawer	Naomi	Part No:			
Linear	Checked	Summer	WCT-USB2-01CF2041L4P3S3E			
X ±0.15	Approved	Macus	Cus. Part No:			
.X ±0.05	Date	2017.07.06	WCT-USB2-01CF2041L4P3S3E			
Angles	Projection	Version	Size	A4	Units	mm
± 3°		A	Scale	1:1	Sheet	1/1